



Základní popis

Řada	Prisma
Kompatibilní řada	Prisma G Prisma Pack 250
Typ produktu nebo součásti	Montážní deska
Příslušenství / náhradní díly	Instalační příslušenství
Instalované zařízení	Compact : pevná INS250 - řízení: přímá přední otočná rukojeť - vodorovná instalace Compact : pevná INV250 - řízení: přímá přední otočná rukojeť - vodorovná instalace Easypact : pevná CVS100...160 ne ochrana proudovým chráničem - řízení: páčka - vodorovná instalace Easypact : pevná CVS250 ne ochrana proudovým chráničem - řízení: páčka - vodorovná instalace Compact : pevná INV100 - řízení: přímá přední otočná rukojeť - vodorovná instalace Compact : pevná INV160 - řízení: přímá přední otočná rukojeť - vodorovná instalace Compact : pevná INV200 - řízení: přímá přední otočná rukojeť - vodorovná instalace Compact : pevná NSX100...160 ne ochrana proudovým chráničem - řízení: páčka - vodorovná instalace Compact : pevná NSX250 ne ochrana proudovým chráničem - řízení: páčka - vodorovná instalace
Popis pólů	1 x 3P : pevná : NSX100...160 vodorovná instalace 1 x 4P : pevná : NSX100...160 vodorovná instalace 1 x 3P : pevná : NSX250 vodorovná instalace 1 x 4P : pevná : NSX250 vodorovná instalace 1 x 4P : pevná : CVS100...160 vodorovná instalace 1 x 3P : pevná : CVS100...160 vodorovná instalace 1 x 4P : pevná : CVS250 vodorovná instalace 1 x 3P : pevná : CVS250 vodorovná instalace 1 x 3P : pevná : INS250 vodorovná instalace 1 x 4P : pevná : INS250 vodorovná instalace 1 x 3P : pevná : INV100 vodorovná instalace 1 x 4P : pevná : INV100 vodorovná instalace 1 x 3P : pevná : INV250 vodorovná instalace 1 x 4P : pevná : INV250 vodorovná instalace 1 x 3P : pevná : INV160 vodorovná instalace 1 x 4P : pevná : INV160 vodorovná instalace 1 x 3P : pevná : INV200 vodorovná instalace 1 x 4P : pevná : INV200 vodorovná instalace

Vyhlasenie: Táto dokumentácia neurčuje náhradu a nemá slúžiť na určenie vhodnosti a spoľahlivosti týchto produktov na špecifické použítie spotrebiteľmi.

Doplňky

Popis rozváděče/skříně	Samostatně stojící rozvaděč - šířka 600 mm Nástěnná montáž rozvaděče - šířka 600 mm Samostatně stojící rozvaděč - šířka 850 mm Rozvaděč Pack - width 600 mm Floor-standing enclosure + duct - width 600 + 300 mm Wall-mounted enclosure + duct - width 600 + 300 mm
Pocet vert. modulu (50 mm)	5 module(s) : CVS100...160 without earth leakage protection , direct with long terminal shield in 600 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure) 5 module(s) : CVS100...160 without earth leakage protection , direct with long terminal shield in 600 mm Wide wall-mounted enclosure (cable coming from top or bottom of enclosure) 4 module(s) : CVS100...160 without earth leakage protection , direct with long terminal shield in 600 + 300 mm Wide floor-standing enclosure + duct (cable coming from top or bottom of enclosure) 4 module(s) : CVS100...160 without earth leakage protection , direct with long terminal shield in 600 + 300 mm Wide wall-mounted enclosure + duct (cable coming from top or bottom of enclosure) 4 module(s) : CVS100...160 without earth leakage protection , direct with long terminal shield in 850 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure) 6 module(s) : CVS100...160 without earth leakage protection , direct with long terminal shield in 600 mm Wide Pack enclosure (cable coming from top or bottom of enclosure) 5 module(s) : CVS250 without earth leakage protection , direct with long terminal shield in 600 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure) 5 module(s) : CVS250 without earth leakage protection , direct with long terminal shield in 600 mm Wide wall-mounted enclosure (cable coming from top or bottom of enclosure) 4 module(s) : CVS250 without earth leakage protection , direct with long terminal shield in 600 + 300 mm Wide floor-standing enclosure + duct (cable coming from top or bottom of enclosure) 4 module(s) : CVS250 without earth leakage protection , direct with long terminal shield in 600 + 300 mm Wide wall-mounted enclosure + duct (cable coming from top or bottom of enclosure) 4 module(s) : CVS250 without earth leakage protection , direct with long terminal shield in 850 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure) 6 module(s) : CVS250 without earth leakage protection , direct with long terminal shield in 600 mm Wide Pack enclosure (cable coming from top or bottom of enclosure) 5 module(s) : INS250, connection block in 600 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure) 5 module(s) : INS250, connection block in 600 mm Wide wall-mounted enclosure (cable coming from top or bottom of enclosure) 4 module(s) : INS250, direct with long terminal shield in 600 + 300 mm Wide floor-standing enclosure + duct (cable coming from top or bottom of enclosure) 4 module(s) : INS250, direct with long terminal shield in 600 + 300 mm Wide wall-mounted enclosure + duct (cable coming from top or bottom of enclosure) 5 module(s) : INS250, direct with long terminal shield in 600 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure) 5 module(s) : INS250, direct with long terminal shield in 600 mm Wide wall-mounted enclosure (cable coming from top or bottom of enclosure) 5 module(s) : INS250, connection block in 600 + 300 mm Wide floor-standing enclosure + duct (cable coming from top or bottom of enclosure) 5 module(s) : INS250, connection block in 600 + 300 mm Wide wall-mounted enclosure + duct (cable coming from top or bottom of enclosure) 5 module(s) : INS250, connection block in 850 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure) 5 module(s) : INV100, connection block in 600 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure) 5 module(s) : INV100, connection block in 600 mm Wide wall-mounted enclosure (cable coming from top or bottom of enclosure) 4 module(s) : INV100, direct with long terminal shield in 600 + 300 mm Wide floor-standing enclosure + duct (cable coming from top or bottom of enclosure) 4 module(s) : INV100, direct with long terminal shield in 600 + 300 mm Wide wall-mounted enclosure + duct (cable coming from top or bottom of enclosure) 5 module(s) : INV100, direct with long terminal shield in 600 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure) 5 module(s) : INV100, direct with long terminal shield in 600 mm Wide wall-mounted enclosure (cable coming from top or bottom of enclosure) 5 module(s) : INV100, connection block in 600 + 300 mm Wide floor-standing enclosure + duct (cable coming from top or bottom of enclosure) 5 module(s) : INV100, connection block in 600 + 300 mm Wide wall-mounted enclosure + duct (cable coming from top or bottom of enclosure) 5 module(s) : INV100, connection block in 850 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure) 4 module(s) : INV100, direct with long terminal shield in 850 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure) 5 module(s) : INV160, connection block in 600 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure) 5 module(s) : INV160, connection block in 600 mm Wide wall-mounted enclosure (cable coming from top or bottom of enclosure)

6 module(s) : NSX100...160 without earth leakage protection , connection block in 600 mm Wide Pack enclosure (cable coming from top or bottom of enclosure)
 6 module(s) : NSX100...160 without earth leakage protection , direct with long terminal shield in 600 mm Wide Pack enclosure (cable coming from top or bottom of enclosure)
 5 module(s) : NSX250 without earth leakage protection , connection block in 600 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure)
 5 module(s) : NSX250 without earth leakage protection , connection block in 600 mm Wide wall-mounted enclosure (cable coming from top or bottom of enclosure)
 4 module(s) : NSX250 without earth leakage protection , direct with long terminal shield in 600 + 300 mm Wide floor-standing enclosure + duct (cable coming from top or bottom of enclosure)
 4 module(s) : NSX250 without earth leakage protection , direct with long terminal shield in 600 + 300 mm Wide wall-mounted enclosure + duct (cable coming from top or bottom of enclosure)
 5 module(s) : NSX250 without earth leakage protection , direct with long terminal shield in 600 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure)
 5 module(s) : NSX250 without earth leakage protection , direct with long terminal shield in 600 mm Wide wall-mounted enclosure (cable coming from top or bottom of enclosure)
 5 module(s) : NSX250 without earth leakage protection , connection block in 600 + 300 mm Wide floor-standing enclosure + duct (cable coming from top or bottom of enclosure)
 5 module(s) : NSX250 without earth leakage protection , connection block in 600 + 300 mm Wide wall-mounted enclosure + duct (cable coming from top or bottom of enclosure)
 5 module(s) : NSX250 without earth leakage protection , connection block in 850 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure)
 4 module(s) : NSX250 without earth leakage protection , direct with long terminal shield in 850 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure)
 6 module(s) : NSX250 without earth leakage protection , connection block in 600 mm Wide Pack enclosure (cable coming from top or bottom of enclosure)
 6 module(s) : NSX250 without earth leakage protection , direct with long terminal shield in 600 mm Wide Pack enclosure (cable coming from top or bottom of enclosure)

Podmínky použití	Need additional plate (2M high) when installation of device is in horizontal
Výška	200 mm
Šířka	600 mm
Hmotnost přístroje	1,16 kg
Povrchová úprava	Matný Hladký
Stupeň ochrany	Elektroforézní ošetření a polyesterový za horka nanášený epoxidový prášek
Barva	Bílá RAL 9001

Prostředí

Standardy	IEC 61439-2
Certifikace výrobku	ASEFA

Nabídka udržitelnosti

Udržitelný stav nabídky	Výrobek Green Premium
RoHS	Vyhovuje - od 0807 - Prohlášení o shodě Schneider Electric Prohlášení o shodě Schneider Electric
REACH	Odkaz neobsahuje SVHC nad mezní hodnotou Odkaz neobsahuje SVHC nad mezní hodnotou
Dokument o ekologickém profilu	Dostupný Vplyv na životné prostredie
Instrukce o ukončení životnosti výrobku	Standardní recyklaci výrobku

Záruční lhůta

Záruční lhůta	18 měsíců
---------------	-----------